



master

Master Optimum R3

Textured Lightblock Roll-Up Film PET + PVC



Thickness & Weight

265 µm – 290 g/m²

Roll Widths & Lengths

914mm-30m
1067mm-30m
1542mm-30m

Recommended conditions

Printroom 15°C - 30°C, 30% - 65% RH
For use -40°C - 80°C, 10% - 90% RH
For storage 10°C - 20°C, 20% - 50% RH

Shelf Life 24 months after delivery
(under recommended storage conditions)

Compatibility

Mid Solvent



Eco Solvent



Latex



UV



Characteristics

- Black back 98% opacity
- PVC frontside for easy printing + PET backside for optimal stay-flat
- Lightly textured surface
- Suitable for indoor and outdoor use
- Scratch resistant, no need for lamination
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness

Applications

- Roller banner displays

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "Gas-out" after printing. This can be achieved by leaving the prints face up, ideally for 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

APPFACTORY - Inspired by print applications

+329 331 53 88

info@appfactorydigital.com

www.appfactorydigital.com