



master

Master 15CC

Wide Format Inkjet Transparent Cling Film



Thickness & Weight

165 µm – 155 g/m2

Roll Widths & Lengths

1372mm-30.5m

Recommended conditions

Printroom 15°C - 30°C, 30% - 65% RH

For use -40°C - 80°C, 10% - 90% RH

For storage 10°C - 20°C, 20% - 50% RH

Shelf Life 24 months after delivery (under recommended storage conditions)

Compatibility

Mid Solvent

Eco Solvent

Latex

UV

N/A

N/A

✓✓✓

✓✓✓

Characteristics

- Unique low tack coating for application to smooth surfaces (glass/acrylic/sheet metal)
- High repositionable – no residue
- Dry or wet application
- 2 year outdoor UV stability
- Face & liner made 100% from PP
- PVC Free

Applications

- Eye-catching window displays
- Temporary signage
- Promotional decals
- Seasonal promotions

NOTICE: The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

APPFACTORY - Inspired by print applications

+32 9 331 53 88

info@appfactorydigital.com

www.appfactorydigital.com